

POWER SUPPLY REQUIREMENTS
CHILLER

Model No.	Volume m ³	External Size	Rivacold Model	Power Supply ¹	Type C Breaker ²
1616C	4.24	1600 x 1600	FTM003	16amp	16amp
1622C	6	1600 x 2200	FTM006	16amp	16amp
1624C	6.59	1600 x 2400	FTM007	16amp	16amp
1628C	7.76	1600 x 2800	FTM007	16amp	16amp
1634C	9.52	1600 x 3400	FTM009	16amp	16amp
1636C	10.11	1600 x 3600	FTM009	16amp	16amp
2216C	6	2200 x 1600	FTM006	16amp	16amp
2222C	8.49	2200 x 2200	FTM009	16amp	16amp
2224C	9.33	2200 x 2400	FTM009	16amp	16amp
2228C	11.42	2200 x 2800	FTM016	32amp	16amp
2234C	13.49	2200 x 3400	FTM016	32amp	16amp
2236C	14.32	2200 x 3600	FTM016	32amp	16amp
2416C	6.59	2400 x 1600	FTM007	16amp	16amp
2422C	9.33	2400 x 2200	FTM009	16amp	16amp
2424C	10.24	2400 x 2400	FTM009	16amp	16amp
2428C	12.54	2400 x 2800	FTM016	16amp	16amp
2434C	15.39	2400 x 3400	FTM016	32amp	16amp
2436C	15.72	2400 x 3600	FTM016	32amp	16amp
2816C	7.76	2800 x 1600	FTM007	16amp	16amp
2822C	11.42	2800 x 2200	FTM016	32amp	16amp
2824C	12.54	2800 x 2400	FTM016	32amp	16amp
3416C	9.52	3400 x 1600	FTM009	16amp	16amp
3422C	13.49	3400 x 2200	FTM016	32amp	16amp
3424C	15.39	3400 x 2400	FTM016	32amp	16amp
3616C	10.11	3600 x 1600	FTM009	16amp	16amp
3622C	14.32	3600 x 2200	FTM016	32amp	16amp
3624C	15.72	3600 x 2400	FTM016	32amp	16amp

FREEZER

Model No.	Volume m ³	External Size	Rivacold Model	Power Supply ¹	Type C Breaker ²
1616F	4.24	1600 x 1600	FTL006	16amp	16amp
1622F	6	1600 x 2200	FTL009	16amp	16amp
1624F	6.59	1600 x 2400	FTL012	32amp	16amp
1628F	7.76	1600 x 2800	FTL012	32amp	16amp
1634F	9.52	1600 x 3400	FTL012	32amp	16amp
1636F	10.11	1600 x 3600	FTL012	32amp	16amp
2216F	6	2200 x 1600	FTL009	16amp	16amp
2222F	8.49	2200 x 2200	FTL012	32amp	16amp
2224F	9.33	2200 x 2400	FTL012	32amp	16amp
2228F	11.42	2200 x 2800	FTL016	32amp	16amp
2234F	13.49	2200 x 3400	FTL016	32amp	16amp
2236F	14.32	2200 x 3600	FTL016	32amp	16amp
2416F	6.59	2400 x 1600	FTL012	32amp	16amp
2422F	9.33	2400 x 2200	FTL012	32amp	16amp
2424F	10.24	2400 x 2400	FTL012	32amp	16amp
2428F	12.54	2400 x 2800	FTL016	32amp	16amp
2434F	15.39	2400 x 3400	FTL016	32amp	16amp
2436F	15.72	2400 x 3600	FTL016	32amp	16amp
2816F	7.76	2800 x 1600	FTL012	32amp	16amp
2822F	11.42	2800 x 2200	FTL016	32amp	16amp
2824F	12.54	2800 x 2400	FTL016	32amp	16amp
3416F	9.52	3400 x 1600	FTL012	32amp	16amp
3422F	13.49	3400 x 2200	FTL016	32amp	16amp
3424F	15.39	3400 x 2400	FTL016	32amp	16amp
3616F	10.11	3600 x 1600	FTL012	32amp	16amp
3622F	14.32	3600 x 2200	FTL016	32amp	16amp
3624F	15.72	3600 x 2400	FTL016	32amp	16amp

Important Information:

Please ensure the correct power supply is installed prior to the delivery of the coldroom

¹ Single Phase Power Supply. Commando Socket within 2 metres of the Monoblock Unit position to suit AMP rating of the selected unit

i.e 16amp / 32amp

² Single Phase Type C Motor Rated Breaker at the distribution board to suit AMP rating of the selected unit

i.e 16amp / 32amp